








Model No. & Drive-Point Device	Installation Method	Applications	Screened Lengths/Port Diameters	Materials	Tubing	Connecting Pipe	
601 Standpipe Piezometers 	Placed in a borehole or pushed into suitable ground	<ul style="list-style-type: none"> • water level monitoring • permeability measurements • slope stability investigations • dewatering drainage operations • construction control • air sparging • metals sampling 	6", 1 ft, 2 ft, 3 ft tips with 3/8" dia. port intakes	<ul style="list-style-type: none"> • PVC • 60 micron Vyon filter • Neoprene washer 	None	3/4" ID PVC riser pipe and slip couplings	
615 Drive-Point Piezometers 	Direct push (manual slide hammer) or drilling methods	<ul style="list-style-type: none"> • water level measurement • groundwater sampling, including VOCs • base flow monitoring in stream beds • contaminant plume delineations • soil gas sampling • UST monitoring • sparge points • low cost, minimal disturbance site assessment 	6", 1 ft tips (1 ft extensions available) with 3/8" dia. port intakes	<ul style="list-style-type: none"> • Stainless steel tip and shields • 50 mesh stainless steel screens 	5/8" OD (w barb) LDPE or PTFE	3/4" NPT steel drive pipe and couplings	
		615 (w barb)  <ul style="list-style-type: none"> • water or vapor sampling • water level measurement 					
		615N (no barb)  <ul style="list-style-type: none"> • water level measurement • water sampling • water level datalogging (using Levelogger and 1" to 3/4" reducer coupling) 					
		615C (w compression fitting)  <ul style="list-style-type: none"> • water or vapor sampling 					
		615S (w shield and w or w/o barb)  <ul style="list-style-type: none"> • water or vapor sampling • water level measurement 					
660 Drive-Point Profiler 	Drill rig hammers or vibrates	standard	<ul style="list-style-type: none"> • high resolution groundwater sampling • contaminant vs. depth profiling • plume delineation 	1.75" dia. tip with single row of 3/16" dia. port intakes	<ul style="list-style-type: none"> • Stainless steel tip • 50 mesh stainless steel screens • Stainless steel push fitting 	5/32" (4 mm) OD LDPE or PTFE	1.75" AW rod and couplings
		grout tip	1.75" dia. tip with single row of 5/32" dia. port intakes				